

	Datasheet	Product Code: CH-600X
		Pages: 1 / 4
		Date: 10.11.2025

ESD Antistatic Chair



Technical Specifications:

Antistatic ESD chairs allow personnel who come into contact with ESD-sensitive products in an office environment to discharge static electricity to the ground via the chair.

High quality conductive fabric covering makes the product very comfortable and discharges static electricity accumulated on the body

through its $<1 \text{ M}\Omega$ fabric resistance and 10^6

– $10^8 \Omega$ grounding resistance.

The chair has a five-point base made of chrome-plated steel. This ensures reliable discharge of electrostatic charge. The chair features a gas column for seat height adjustment and

a seat backrest with height and angle adjustment. The chair is equipped with conductive rubber wheels that prevent scratches on the floor or conductive wheel marks. This feature allows it to work in harmony with antistatic floor coverings and does not damage the surface it is placed on.

The chair is equipped with conductive rubber wheels that prevent scratches on the floor or conductive wheel marks. This feature allows it to work in harmony with antistatic floor coverings and does not damage the surface it is placed on.

Compliant with IEC 61340-5-1:2016



Atom Mühendislik San. Tic. A.Ş.

Web: <http://atommuhendislik.com.tr>

E-mail: info@atommuhendislik.com.tr



	Datasheet	Product Code: CH-600X
		Pages: 2 / 4
		Date: 10.11.2025

Technical Specifications:

Grounding Resistance: 10^6 – 10^8 Ω

Fabric Surface Resistance: 10^5 – 10^6 Ω

Fabric Abrasion Resistance: 60,000 cycles

Compliant Standards:

- EN 61340-5-1 – “Electrostatics – Part 5-1: Protection of electronic devices against electrostatic discharge – General requirements”;
- EN 1335-1– “Office furniture – Office task chairs – Part 1: Dimensions – Dimensioning”
- PN-EN 1335-2– “Office furniture – Office task chairs – Part 2: Safety requirements”;
- PN-EN 1335-3– "Office furniture. Office task chairs. Test methods";
- PN-EN 1022 – “Furniture – Seating – Stability determination”.

Chairs / Order Codes:

CH-6001: ESD Chair (475-600 mm)

Seat Height Adjustment Range: 475- 600 mm

Seat Dimensions: 440 x 460 mm

Back Dimensions: 430 x 500 mm

CH-6002: ESD Chair (545-745 mm)

Seat Height Adjustment Range: 545-745 mm

Seat Dimensions: 440 x 460 mm

Back Dimensions: 430 x 500 mm

CH-6003: ESD Chair (650-890 mm)

Seat Height Adjustment Range: 650-890 mm

Compliant with IEC 61340-5-1:2016



Atom Mühendislik San. Tic. A.Ş.

Web: <http://atommuhendislik.com.tr>

E-mail: info@atommuhendislik.com.tr



	Datasheet	Product Code: CH-600X
		Pages: 3 / 4
		Date: 10.11.2025

Seat Dimensions: 440 x 460 mm

Back Dimensions: 430 x 500 mm

Spare/Extra Products:

CZ-KESD: Conductive Chair Arm

CH-KP: Foot Support

CZ-KCZP: Plastic Wheel

CZ-KCZ/K1: Rubber Wheel

CZ-KCZ/K5: Stainless Steel Wheel

CH-KCZ/K7: Conductive Fixed Foot



CZ-KESD



CH-KP

Compliant with IEC 61340-5-1:2016



Atom Mühendislik San. Tic. A.Ş.

Web: <http://atommuhendislik.com.tr>

E-mail: info@atommuhendislik.com.tr



**CZ-KCZP****CH-KCZ/K5****CH-KCZ/K1****CH-KCZ/K7****Compliant with IEC 61340-5-1:2016**