

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SOLAR-FLUX EO-S-009 (2.5, B, C)

Further trade names

Fluxes / Elektronik Flux / SOLAR-FLUX

#6209 EO-S-009 [1,8%] (UFI: 836J-S0D7-D00F-0SJU)

#6268 EO-S-009 / 2.5 [2,5%] (UFI: 45CJ-N03N-F00N-1WXN)

#6269 EO-S-009 / B [3%] (UFI: W7CJ-40T1-S005-Q8HQ)

#6270 EO-S-009 / C [4%] (UFI: HACJ-N0GF-200N-CM3S)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Industrial use of processing aids.

Surface active agent

Uses advised against

Intermediate (precursor)

1.3. Details of the supplier of the safety data sheet

Company name:	EMIL OTTO	
	Flux- und Oberflächentechnik GmbH	
Street:	Eltviller Landstrasse 22	
Place:	D-65346 Eltville-Erbach	
Telephone:	+49 6123 7046-0 /-28	Telefax: +49 6123 7046-15
E-mail:	andre.bremser@emilotto.de	
Contact person:	André Bremser	Telephone: +49 6123 7046-28
E-mail:	andre.bremser@emilotto.de	
Internet:	www.emilotto.de	
Responsible Department:	Laborleitung	
	Betrieblich verantwortliche Person (WHG, REACH, Gefahrstoffe, Gefahrgut)	
	24h: 00491777879007	
	0049613119240 (Giftinfo Mainz)	

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 2 of 16

Hazard categories:

Flammable liquids: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.

P270 Do not eat, drink or smoke when using this product.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 3 of 16

	water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use @1501.B150664 to extinguish.
P235	Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to @1501.B015816Consult the local waste disposal expert about waste disposal.Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)"..

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards

See attached safety data sheets and/or usage instructions.

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Single packagings <125 ml = Restricted to professional users.

See attached safety data sheets and/or usage instructions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Contains: Alcohol.
Contains: Activator
Contains: resin. (RESIN)

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 4 of 16

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			90-100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
123-99-9	Dicarboxylic acid mixture (C9)			1-5 %
	204-669-1			
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
123-99-9	204-669-1	Dicarboxylic acid mixture (C9)	1-5 %
	dermal: LD50 = >10000 mg/kg; oral: LD50 = >4000 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs.

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 5 of 16

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No known symptoms to date.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

D powder.

5.2. Special hazards arising from the substance or mixture

Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 6 of 16

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13 Treat the recovered material as prescribed in the section on waste disposal.

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary.

Further information on handling

Avoid contact with skin and eyes.

Do not spray on naked flames or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Always close containers tightly after the removal of product. Keep container tightly closed. Protect from direct sunlight.

7.3. Specific end use(s)

Surface active agent

Further information: refer to Technical Data Sheet.

SECTION 8: Exposure controls/personal protection

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 7 of 16

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Additional advice on limit values

Use appropriate respiratory protection.

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Additional protection measures for the hands:

Hand protection: EN ISO 374

-CR (polychloroprenes, Chloroprene rubber).

Thickness of glove material: : 0,65mm

penetration time (maximum wearing period): : >120min.

-NBR (Nitrile rubber):.

Thickness of glove material: : 0,4mm

penetration time (maximum wearing period): : >480min.

Breakthrough times and swelling properties of the material must be taken into consideration.

Take recovery periods for skin regeneration.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 8 of 16

Use gloves only once.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Before using check leak tightness / impermeability.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. [In case of inadequate ventilation] wear respiratory protection. Use appropriate respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Filtering device (full mask or mouthpiece) with filter::A

Environmental exposure controls

No special measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless - light yellow
Odour:	Alcohol
Odour threshold:	low

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	80 °C
Flammability:	Flammable liquid and vapour.
Lower explosion limits:	2 g/m ³
Upper explosion limits:	12 g/m ³
Flash point:	12 °C
Auto-ignition temperature:	425 °C
Decomposition temperature:	not determined ASTM D 2879
pH-Value (at 20 °C):	3-6
Viscosity / kinematic:	not determined
Water solubility:	slightly soluble

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 9 of 16

Solubility in other solvents

not determined

Dissolution rate:

not determined

Partition coefficient n-octanol/water:

not determined OECD 117

Dispersion stability:

not determined

Vapour pressure:

48 hPa

(at 20 °C)

Vapour pressure:

236 hPa OECD 104

(at 50 °C)

Density:

0,8 g/cm³

Relative density:

not determined

Bulk density:

not determined NF T 20-053

Relative vapour density:

not determined

Particle characteristics:

not determined

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

98,2% / 97,5% / 97% / 96%

Solid content:

1,8% / 2,5% / 3% / 4%

Sublimation point:

No data available

Softening point:

No data available

Pour point:

not determined

not determined

Viscosity / dynamic:

not determined

Flow time:

not determined

Further Information

In contact with water do not emit flammable gases.

Thermal decomposition at °C: >300

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 10 of 16

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures. May form hazardous decomposition products when exposed to high temperatures.

10.2. Chemical stability

Stability and reactivity: Yes.

In contact with water do not emit flammable gases.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidizing agents, strong., Alkali metals.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Oxidizing agents, strong.

Alkali metals.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

Further information

No special measures are necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 11 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-99-9	Dicarboxylic acid mixture (C9)				
	oral	LD50 >4000 mg/kg	Rat		
	dermal	LD50 >10000 mg/kg	Rat		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Thermal decomposition can lead to the escape of irritating gases and vapours.

12.2. Persistence and degradability

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

12.3. Bioaccumulative potential

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 12 of 16

components (see section 3).

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

12.4. Mobility in soil

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the criteria for classification as PBT or vPvB.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

This substance does not meet the criteria for classification as PBT or vPvB.

Further information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

List of Wastes Code - used product

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 13 of 16

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

Do not allow uncontrolled discharge of product into the environment.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

274 601 640C

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 14 of 16



Classification code: F1
Special Provisions: 274 601 640C
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E
Segregation group: IMDG-Code segregation group not applicable

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 15 of 16

IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid. Do not allow uncontrolled discharge of product into the environment.

14.7. Maritime transport in bulk according to IMO instruments

not determined

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions:	98,2 % / 97,5% / 97% / 96%
---	----------------------------

Directive 2004/42/EC on VOC in paints and varnishes:	98,2 % / 97,5% / 97% / 96%
--	----------------------------

Information according to Directive 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
---	-----------------------

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
--------------------------	--

Water hazard class (D):	1 - slightly hazardous to water
-------------------------	---------------------------------

Additional information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

according to UK REACH Regulation

According to
2020/878/EU

SOLAR-FLUX EO-S-009 (2.5, B, C)

Revision date: 09.01.2025

Product code: 6209

Page 16 of 16

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq: Flammable liquids
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)